










Approvals \*



Rated power [kW/HP]  
Corrective current [A]

Features

Typical applications

Filter family	Nom. voltage	0 100 200 300 400 500					For 50Hz grids	For 60Hz grids	THID <5%	Power factor correction	Load balancing	3-phase / 3-wire	3-phase / 4-wire	For 6-pulse diode rectifiers	For 6-pulse SCR rectifiers	AC Motor drives	DC Motor drives	Welding machines	HVAC installations	Building power distribution	Semiconductor industry	Water / wastewater treatment
		Rated power [kW/HP]	Corrective current [A]																			
FN 3410 	380 - 500VAC	4	400kW																			
FN 3410 HV 	690VAC	7.5	250kW																			
FN 3411 	380 - 500VAC	4	400kW																			
FN 3412 	380 - 480VAC	5	500HP																			
FN 3413 	380 - 480VAC	5	500HP																			
NEW FN 3416 	380 - 500VAC	4	200kW																			
NEW FN 3418 	380 - 480VAC	5	250HP																			
NEW FN 3420 (active) 	200 - 690VAC	30	300																			
FN 3430 (active) 	200 - 415VAC	30	300																			

Note: filters FNxx11xx and FNxx13xx are available on request.

Note: power ratings marked with hatchings are in preparation.

Note: filter FN 3420-200-690-3 are available on request.