



| ALL DIMENSIONS ARE IN mm WITH ±0.20 TOLERANCE OR OTHER SPECIFICITY | |
|--|----------------------------|
| THE LCD | LCD+ODG IC-FPC+LED |
| DRIVING VOLTAGE: | 11.0V |
| LCD TYPE | FSTN/TRANSMISSION/NEGATIVE |
| VIEWING ANGLE: | 12 : 00 |
| LED BACKLIGHT: | BLUE |
| OPERATION TEMP: | -20°C - +70°C |
| DRIVER IC | ST7565P |
| STORAGE TEMP: | -30°C - +80°C |
| DRIVING METHOD: | 1/65 DUTY, 1/9 BIAS |
| CONNECTOR: | FPC |

| PIN NO. | SYMBOL | PIN NO. | SYMBOL |
|---------|--------|---------|--------|
| 1 | /CS1 | 18 | CAP3- |
| 2 | /RES | 19 | CAP1+ |
| 3 | A0 | 20 | CAP1- |
| 4 | WR | 21 | CAP2- |
| 5 | RD | 22 | CAP2+ |
| 6 | D0 | 23 | CAP4- |
| 7 | D1 | 24 | VRS |
| 8 | D2 | 25 | V1 |
| 9 | D3 | 26 | V2 |
| 10 | D4 | 27 | V3 |
| 11 | D5 | 28 | V4 |
| 12 | D6 | 29 | V5 |
| 13 | D7 | 30 | VR |
| 14 | VDD | 31 | C86 |
| 15 | VSS | 32 | P/S |
| 16 | VDOUT | 33 | HPM |
| 17 | CAP5- | 34 | IRS |

