



PIN FUNCTION NO.	SYMBOL
1	NC
2	NC
3	VDD
4	C86
5	VSS
6	V0
7	V4
8	V3
9	V2
10	V1
11	CAP2-
12	CAP2+
13	CAP1+
14	CAP1-
15	CAP3+
16	VOUT
17	VSS
18	D7
19	D6
20	D5
21	D4
22	D3
23	D2
24	D1
25	D0
26	/RD
27	/WR
28	A0
29	/RES
30	/CS1
31	NC

- NOTES:
1. DISPLAY TYPE: FSN
  2. VIEWING DIRECTION: 6 O'CLOCK
  3. DRIVE METHOD: 1/65 DUTY 1/9 BIAS
  4. POLARIZER MODE: TRANSELECTIVE/POSITIVE
  5. LCD DRIVE VOLTAGE: 8.2V
  6. LOGIC POWER SUPPLY VOLTAGE: 3.0V
  7. OPERATING TEMP: -20 C--+70 C
  8. STORAGE TEMP: -30 C--+80 C
  9. DRIVER/CONTROLLER IC: NT7534H-BDT
  10. CONNECTION TYPE: HFC
  11. OTHER TOLERANCE: ±0.2

DETAIL DOTS  
SCALE: 10X

DETAIL "A"  
SCALE: 3X