



SG16032B (160 CHARACTERS X32 LINES)

FEATURES

- BUILT-IN CONTROLLER (SBN0080G)
- +5 V POWER SUPPLY
- 1/32 DUTY CYCLE
- 8-BIT PARALLEL INTERFACE

MECHANICAL DATA

ITEM	DIMENSIONS	UNIT
Module Size (W x H x T)	122.0 x 44.0 x 13.6	mm
Viewing Area (W x H)	99.0 x 24.0	mm
Active Area (W x H)	94.36 x 19.16	mm
Dot Size (W x H)	0.55 x 0.56	mm
Dot Pitch (W x H)	0.59 x 0.60	mm

INTERFACE PIN CONNECTIONS

NO.	SYMBOL	LEVEL	FUNCTION
1	V _{SS}	0V	Supply Ground
2	V _{DD}	5V	Supply Voltage
3	V _o	-	LCD driver supply voltage
4	A _o	H/L	Data Type select signal
5	CS1	H	Chip Select Signal for IC1
6	CS2	H	Chip Select Signal for IC2
7	NC	---	No Connection
8	E	H-->L	Enable Signal
9	R/W	H/L	Read/Write
10~17	DB0~DB7	H/L	Data Bus Line
18	REST	H/L	Reset Signal
19	A	3.2V	LED Power (+)
20	K	0V	LED Power (-)

ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	MIN.	TYP.	MAX.	UNIT
Supply Voltage For Logic	V _{DD} -V _{SS}	0	-	7	V
Supply Voltage For LCD Drive	V _{DD} -V _o	0	-	10	V
Input Voltage	V _I	V _{SS}	-	V _{DD}	V

ELECTRICAL CHARACTERISTICS

ITEM	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	
Supply Voltage For Logic	V _{DD} -V _{SS}	-	4.5	5	5.5	V	
Supply Voltage For LCD	V _{DD} -V _o	V _{DD} =5V Ta=25	4.5	4.8	5.2	V	
Supply Current	I _{DD}	V _{DD} =5V	-	2.5	4.5	mA	
Input Voltage	"HIGH" Level	V _{IH}	-	2.2	-	V _{DD}	V
	"LOW" Level	V _{IL}	-	-	-	0.6	V
Output Voltage	"HIGH" Level	V _{OH}	-	2.4	-	V	V
	"LOW" Level	V _{OL}	-	-	-	0.4	V

EXTERNAL DIMENSIONS

